



1 带内螺纹的内六角螺钉, 用于安装附件
Hexagon socket head cap screws with internal thread for mounting accessories

2 调节螺钉, 用于调节可调缓冲
Regulating screw for adjustable end-position cushioning

3 沟槽, 用于安装接近开关D-Z73
Slot for proximity sensor D-Z73

+ =加上行程长度
Plus stroke length

缸径 Bore size (mm)	AM	\varnothing Bd11	BG	E	EE	J2	J3	KK	L1	L2
32	22	30	16	45	Rc1/8	6	5.2	M10x1.25	18	94
40	24	35	16	54	Rc1/4	8	6	M12x1.25	21.5	105
50	32	40	17	64	Rc1/4	10.4	8.5	M16x1.5	28	106
63	32	45	17	75	Rc3/8	12.4	10	M16x1.5	28.5	121
80	40	45	17	93	Rc3/8	12.5	8	M20x1.5	34.7	128
100	40	55	17	110	Rc1/2	12	10	M20x1.5	38.2	138
125	54	60	22	134	Rc1/2	13	8	M27x2	46	160

缸径 Bore size (mm)	L7	\varnothing MM	PL	RT	TG	VA	VD	WH	ZJ	\varnothing 1	\varnothing 2	\varnothing 3
32	3.3	12	15.6	M6	32.5	4	10	26	120	10	16	6
40	3.6	16	147	M6	38	4	10.5	30	135	13	18	6
50	5.1	20	14	M8	46.5	4	11.5	37	143	17	24	8
63	6.6	20	17	M8	56.5	4	15	37	158	17	24	8
80	10.5	25	16.4	M10	72	4	15.7	46	174	22	30	6
100	8	25	18.8	M10	89	4	19.2	51	189	22	30	6
125	14	32	18	M12	111	6	20.5	65	225	27	36	8